



## JLN-18160 Natural

### SELF-ADHESIVE REINFORCED KRAFT PAPER TAPE

Physical Properties		Standard	Metric	Test Method	
Color		Natural			
Composite Layer Adhesive		Polymeric Copolymer			
Adhesive		Hot Melt Adhesive			
Total Thickness	6.9 mils	0.175 mm	ASTM D-3652	GB/T7125	
Peel Adhesion 90°	90 oz/in	25 N/25mm	ASTM D-3330	GB/T2792	
Holding Power	>48 h	>48 h	ASTM D-3654	GB/T4851	
Tensile Strength	53 lbs/in	290 N/25mm	ASTM D-3759	GB/T7753	
Elongation at Break	3-5%	3-5%	ASTM D-3759	GB/T7753	
Service Tem.--Mini	23°F	-5°C	BC/BD-220SE	BC/BD-220SE	
Service Tem.--Max	140°F	60°C	DHG-9055A	DHG-9055A	
Reinforcement	MD	72mm 110 (1-1-1-1-1) Fiberglass			
	CD	28mm 150 (1-1-1) Fiberglass Diamond Pattern			
Backing	Top Ply: 25 lb (40 g/m <sup>2</sup> ) Kraft Paper				
	Bottom Ply: 25 lb (40 g/m <sup>2</sup> ) Kraft Paper				

#### DESCRIPTION

JLN-18160 Self-adhesive reinforced kraft paper tape is a quick, reliable, economical, pressure-sensitive tape, which can improve the efficiency of the packaging line. Strong initial adhesion, strong airtightness, and reinforcement technology make this tape have better tensile strength than ordinary tape, and it is not easy to steal.

#### PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads.

#### STORAGE CONDITION

It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 4°C to 26°C and the humidity shall be between 40% and 50%. Rotate inventory recommended.

The above properties and results obtained refer to the average values of laboratory testing carried out on the samples of JIALONG product. JIALONG does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. JIALONG strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. JIALONG assumes no responsibility for any damage or injury sustained as a result of the use of its products.

#### FUJIAN JIALONG ADHESIVE TAPE CO., LTD.

No.11 Xiazhai Road, Jiulong Industry Park, Hua An, Zhangzhou, Fujian 363000 China.  
Tel:+86-592-207-5506  
info@jl3tape.com <http://www.jl3tape.com>

